

Adjustable Focus Aspheric Fiber Collimator 650-1050nm (Focal Length 11mm Beam Waist Diameter 2.35 FC/APC)



● **Product Description**

The design uses springs to assemble a suitable optical lens inside the mechanical part, which is used for the collimator output of the optical fiber beam and can also be used for fiber-to-fiber coupling. By rotating the sleeve outside the collimator, the internal optical lens can be translated forward and backward along the optical axis, thereby adjusting the distance between the lens and the end face of the optical fiber to obtain different spot sizes.

● Product features

Three AR-coated aspheric lens options: 350- 700nm, 650-1050nm, 1050-1620nm 、 Use with compatible connectors to achieve diffraction-limited performance 、 Alignment error during adjustment <15mrad

● Part Number

MP-CLM-NIR-2.35-PA


● Application area

Fiber Laser Systems | Optical Communication & Sensing | Industrial Inspection | Medical Equipment | Scientific Optical Platforms

● Core parameters

Wavelength	Focal Length	Beam Waist Diameter
650-1050nm	11mm	2.35

● Dimension Drawing



● General Parameters

F=4.5m adjustable focus aspheric collimator

Focal length	NA	Waist diameter	Lens coating wavelength	Far-field divergence angle of collimated light beam	Maximum waist distance	Input Fiber MFD	Distance from optical fiber to lens	Connector Type	Transmittance
4.5m	0.54	0.86	400~700nm R<0.5%	0.045°	530mm	3.5μm	2.4-4.9mm	FC/PC FC/APC	>90%
4.5m	0.54	0.98	650~1050nm R<0.5%	0.062°	453mm	5μm	2.4-4.9mm		

4.5m	0.5	0.87	1050~1	0.12°	194mm	10.4μ	2.4-4.9		
m	4		700nm			m	mm		
			R<0.5%						
F=7.5m adjustable focus aspheric collimator									
focal length	NA	Waist diam eter	Lens coating wavele ngth	Far-field divergence angle of collimated beam	Maximum waist distance	Input Fiber MFD	Distance from optical fiber to lens	Connec tor Type	Trans mitta nce
7.5m	0.3	1.35	400-700 nm R<0.5%	0.027°	1435mm	3.5μ m	4.2-6.8 mm	FC/PC FC/APC	>90%
7.5m	0.3	1.6	650~10 50nm R<0.5%	0.038°	1225mm	5μm	4.2-6.8 mm		
7.5m	0.3	1.44	1050~1 700nm R<0.5%	0.08°	521mm	10.4μ m	4.2-6.8 mm		
F=11mm adjustable focus aspheric collimator									

focal length h	NA Le ns	Waist diam eter	Lens coating wavele ngth	Far-field divergence angle of collimated light beam	Maximum waist distance	Input Fiber MFD	Distance from optical fiber to lens	Connec tor Type	Trans mitta nce
11m m	0.3	1.96	400-700 nm R<0.5%	0.018°	3080mm	3.5μ m	8.6- 10.9 mm	FC/PC FC/APC	>90%
11 mm	0.3	2.35	650~10 50nm R<0.5%	0.026°	2631mm	5μm	8.6-10.9 mm		
11 mm	0.3	2.1	1050-17 00nm R<0.5%	0.055°	1115mm	10.4μ m	8.6-10.9 mm		