

1064nm In-line Polarizer Hi1060 Fiber



- **Product Description**

Idealphotonics' In-line Polarizer is designed to pass a specified polarization and block other polarizations. Its function is to convert unpolarized light into linearly polarized light to achieve a high extinction rate. It is also used to improve the extinction rate of precision measurement systems, fiber optic sensors, high-speed test instruments, etc. We have designed an in-line polarizer specifically for the ring gyro system, and its components are

tested under full temperature conditions. In addition, its mini size is very suitable for our cost-effective fiber optic gyro system.

● Product features

High extinction ratio、 Low insertion loss、 High return loss、 Full wavelength selection、 Wide operating bandwidth

● Part Number

MP-ILP-1064-30-SA-SA

● Application area

Communication system、 Test instruments、 Fiber optic gyroscopes、 Research、 Fiber optic current transformers (FOCT)、 Fiber optic sensors

● Core parameters

Center Wavelength	Typical Extinction ratio	Output Fiber	Connector
1064nm	30dB	Hi1060	FC/APC

● General Parameters

Parameters

Parameters	Unit	value				
Central wavelength	nm	1310, 1550	1064	1030	980	850
Working range wavelength	nm	±50	±30	±30	±10	±10
Insertion loss at 23°C (typical)	dB	0.3	0.4	0.4	0.7	0.8
Insertion loss at 23°C (maximum)	dB	0.5	0.6	0.6	0.9	1
Return loss (minimum)	dB	50	50	50	50	50
Extinction ratio at 23°C (typical)	dB	30	30	30	28	28
Extinction ratio at 23°C (minimum)	dB	28	28	28	25	25
Output power (maximum)	mW	300				
Tensile load (maximum)	N	5				
Input fiber type	°C	SM/PM , Single-mode: (SMF-28E / Hi1060 / SM800) polarization-maintaining:(PM1550/PM980/ PM850)				
Output fiber type	°C	SM/PM				
Connector type	°C	FC/APC X2				
Operating temperature	°C	-5~+70				
Storage temperature	°C	-40~+85				
The default connector key is aligned with the slow axis;						