

1550nm High Temperature Fiber Collimator, MM, Bandwidth \pm 20nm



● Product Description

The high-temperature fiber collimator uses high-temperature resistant optical fiber, high-temperature resistant manufacturing process and materials, which can meet the application environment of working temperature of $-40\sim 220\text{ }^{\circ}\text{C}$. The FC/APC high-temperature resistant connectors specially used for high-temperature devices ensure the stability



of the optical fiber docking signal in high-temperature environment. The product must undergo a 48-hour 220 ° high-temperature reliability test before leaving the factory to ensure the reliability of the device in long-term working in high-temperature environment.

- **Product features**

High temperature resistance、 High reliability

- **Part Number**

MP-CLM-1550-20-MF-PA

- **Application area**

Fiber Optic Devices

- **Core parameters**

Wavelength	Bandwidth	Fiber type	Connector
1550nm	±20nm	MM	FC/APC

- **General Parameters**

Main Parameters:

wavelength	bandwidth	working distance	output	Divergence	package	Insertion	Return	Mode Field	Fiber Type



			beam size	angle		loss	loss	Diameter	
1310nm	± 20nm	≤ 300mm	0.81mm	2.3mrad	Φ 3.4mm	≤ 0.6 dB	≥ 55dB	9.2± 0.4 μm	9/125 Polyimide coating
		300-1000mm	1.27mm	1.7mrad	Φ 4.0mm	≤ 0.9 dB			B
		10mm	0.6mm	20mrad	Φ 3.4mm	≤ 0.5 dB	≥ 30dB	50± 2.5 μm	50/125 Polyimide coating
		10mm	0.75mm	24mrad	Φ 3.4mm	≤ 0.6 dB	≥ 30dB	62.5± 2.5 μm	62.5/125 Polyimide coating



1550nm	± 20nm	≤ 300mm	0.92 mm	2.4mrad	Φ 3.4mm	≤ 0.6 d	≥ 55d	10.4± 0.5um	9/125 Polyimide coating
		300-1000mm	1.45 mm	1.4mrad	Φ 4.0mm	≤ 0.9 d			B
	± 20nm	10mm	0.6mm	20mrad	Φ 3.4mm	≤ 0.5 d	≥ 30d	50± 2.5 um	50/125 Polyimide coating
		10mm	0.75mm	24mrad	Φ 3.4mm	≤ 0.6 d	≥ 30d	62.5± 2.5um	25 Polyimide coating
1650nm	± 20nm	≤ 300mm	0.96 mm	2.4mrad	Φ 3.4mm	≤ 0.6 d	≥ 55d	10.4± 0.5um	9/125 Polyimide coating



		300-100	1.5m	1.4mrad	Φ	\leq			mid
		0mm	m	d	4.0m	0.9 d			coatin
					m	B			g

Appendix 1: Optional Configuration Table

High temperature fiber collimator	Optional Configuration						
Product name	Type	Central wavelength	Bandwidth	Working distance	Connectors	Pigtail	Reserve optional configuration
FCT:High Temperature Fiber Collimator	S:Single Mode	31:1310 nm	A:±20m	F:Fixed working distance	A:FC/APC	Y:With pigtail	
	M:Multimode	55:1550 nm		V:Variable			



				workin g distanc e			
		65:1650 nm					

Appendix 2: Model and Part Number Comparison Table

Part Number	Specification
MP-CLM-1310-20-SF-PA	1310nm High temperature fiber collimator, single mode, bandwidth ± 20 nm, variable working distance, FC/APC, with pigtail
MP-CLM-1310-20-MF-PA	1310nm High temperature fiber collimator, multimode, bandwidth ± 20 nm, variable working distance, FC/APC, with pigtail
MP-CLM-1550-20-SF-PA	1550nm High temperature fiber collimator, single mode, bandwidth ± 20 nm, variable working distance, FC/APC, with pigtail
MP-CLM-1550-20-MF-PA	1550nm High temperature fiber collimator, multimode, bandwidth ± 20 nm, variable working



	distance, FC/APC, with pigtail
MP-CLM-1650-20-SF-PA	1650nm High temperature fiber collimator, single mode, bandwidth \pm 20nm, variable working distance, FC/APC, with pigtail