

## 1512nm high power single mode DFB laser

### 20mW (TO39 package NH3 detection)



- **Product Description**

With optimized optical properties, the 1512nm single-mode DFB is ideal for demanding sensing system applications. The innovative chip design has suppressed high-order longitudinal and transverse modes while providing linear polarization stability. The laser has high output power, narrow linewidth and good consistency and is currently favored by domestic scientific research customers. We currently have in stock wavelength



1512nm DFB for TDLAS oxygen detection, 795nm VCSEL for Rb atomic clock experiments, and 852nm VCSEL for CS atomic cooling.

## ● Product features

Ultra-high output power, Narrow linewidth, Internal TEC and thermistor ,  
2 nm TEC tunability

## ● Part Number

MP-DFB-1512-20-A81-T039

## ● Application area


TDLAS oxygen analysis detection, Optical coherence experiment

## ● Core parameters

Wavelength	Output Power	Package
1512nm	20mW	T039



## ● Dimension Drawing



## ● General Parameters

### Descriptions

Parameter	Symbol	Min	Typical	Max	Unit	Remarks
Incident Wavelength	$\lambda_R$	1512	1512.5	1513	nm	$T=20^\circ$ $C, I_{TEC}=0, P_{OP}=35\text{mw}$
Threshold Current	$I_{TH}$		40		mA	$T=20^\circ\text{C}$
Output Power	$P_{opt}$	10	20	30	mW	$T=0\cdots 50^\circ\text{C}$
Threshold Voltage	$U_{TH}$		1.80		V	
Laser Current	$I_{OP}$			130	mA	$P_{opt}=35\text{mw}$
Laser Voltage	$U_{OP}$		2.0		V	$P_{opt}=35\text{mw}$



<b>Electro-Optic Conversion Efficiency</b>	$\eta_{WP}$		12		%	$P_{opt} = 20 \text{ mw}$
<b>Slope Efficiency</b>	$\eta_s$		0.74		W/A	$T = 20^\circ \text{ C}$
<b>3dB Modulation Bandwidth</b>	$\nu_{3dB}$		3		MHz	$P_{opt} = 20\text{mW}$ (due to ESD protection diode)
<b>Relative Intensity Noise</b>	RIN		-130	-120	dB/Hz	$P_{opt} = 0.3 \text{ mW@} 1 \text{ GHz}$
<b>Wavelength Tuning Current</b>			0.01		nm/mA	
<b>Wavelength Tuning Temperature</b>			0.1		nm/deg	
<b>Thermal Resistance</b>	$R_{thermal}$	3		5	K/mW	
<b>Side Mode Suppression</b>		30			dB	
<b>Beam Divergence</b>	$\theta$	10		25	$^\circ$	$P_{opt} = 35\text{mW}$ , Full 1/e <sup>2</sup> Bandwidth
<b>Spectral Bandwidth</b>	$\Delta\nu$		3		MHz	$P_{opt} = 35\text{mw}$
<b>TEC Current</b>	$I_{TEC}$			1000	mA	Requires appropriate heatsink
<b>NTC Thermistor Resistance</b>		9.5	10.0	10.5	k $\Omega$	$T = 25^\circ \text{ C}$
<b>NTC Temperature Dependency</b>		$10/\exp[3892 \cdot (1/298K - 1/TOP)]$			k $\Omega$	




## Absolute Maximum

Storage Temperature	-40··125°C
Operating Temperature	-20··80°C
Power Dissipation	500 mW
Forward Laser Current	130 mA
Reverse Current	10 mA
Soldering Temperature	270°C


\*(The TEC temperature must be below 70°C)

## Spectrum:






## L-I Curve:




## DFB Linewidth Testing Result:







## Central Wavelength:



## Beam Quality Analysis




## Ammonia Absorption spectral lines



## Pin definition

With TEC pin configuration



## Bottom View

ico	SN#	pin definition	ico	SN#	pin definition
	1	Cooler+		4	Thermistor
	2	LD+		5	LD-
	3	Thermistor		6	Cooler-



## Ordering Information

MP-DFB-□□□□-☆-A8▽-T05

□□□□: wavelength

0760: 760nm

1270: 1270nm

1532: 1532nm

1392: 1392nm

1512: 1512nm

1567: 1567nm

\*\*\*\*\*

1653.7: 1653.7nm

☆: output power

A: 10mW

B: 20mW

▽: wavelength tolerance

1: ±1nm

2: ±2nm