



## 1030nm In-line Polarizer Hi1060 fiber



### ● Product Description

Idealphotonics' In-line Polarizer is designed to pass a specified polarization and block other polarizations. Its function is to convert unpolarized light into linearly polarized light to achieve a high extinction rate. It is also used to improve the extinction rate of precision measurement systems, fiber optic sensors, high-speed test instruments, etc. We have designed an in-line polarizer specifically for the ring gyro system, and its components are tested under full temperature conditions. In addition, its mini size is very suitable for our cost-effective fiber optic gyro system



## ● Product features

High extinction ratio、 Low insertion loss、 High return loss、 Full wavelength optional、 Wide operating bandwidth

## ● Part Number

MP-ILP-1030-30-SA-SA

## ● Application area

Communication system、 Test instruments、 Fiber optic gyroscopes、 Research、 Fiber optic current transformers (FOCT)、 Fiber optic sensors

## ● Core parameters

Center Wavelength	Typical Extinction ratio	Output Fiber	Connector
1030nm	30dB	Hi1060	FC/APC

## ● General Parameters

### Parameters

Parameters	Unit	value					
		1310	1550	1064	1030	980	850
Central wavelength	nm	1310	1550	1064	1030	980	850
Working range wavelength	nm	±50	±30	±30	±30	±10	±10
Insertion loss at 23°C (typical)	dB	0.3	0.4	0.4	0.4	0.7	0.8
Insertion loss at 23°C	dB	0.5	0.6	0.6	0.6	0.9	1



Parameters	Unit	value				
(maximum)						
Return loss (minimum)	dB	50	50	50	50	50
Extinction ratio at 23°C (typical)	dB	30	30	30	28	28
Extinction ratio at 23°C (minimum)	dB	28	28	28	25	25
Output power (maximum)	mW	300				
Tensile load (maximum)	N	5				
Input fiber type	°C	SM/PM , Single-mode: (SMF-28E / Hi1060 / SM800) polarization-maintaining:(PM1550/PM980/ PM850)				
Output fiber type	°C	SM/PM				
Connector type	°C	FC/APC X2				
Operating temperature	°C	-5~+70				
Storage temperature	°C	-40~+85				
Default connector keys are aligned with the slow axis;						