

1310nm Polarization-Maintaining Single-Stage Fiber Isolator



- **Product Description**

IdealPhotonics' optical isolator products maintain excellent back-reflection isolation performance under any polarization state. They feature low insertion loss, high isolation, high return loss, low polarization-dependent loss (PDL), low polarization mode dispersion (PMD), a wide operating wavelength and temperature range, and an epoxy-free optical path. These characteristics make them a cost-effective solution for communication networks. This series of products is suitable for



erbium-doped amplifiers, wavelength division multiplexing (WDM) systems, fiber optic equipment, and lasers.

- **Product features**

Wide operating wavelength range & wide operating temperature range、
 Low insertion loss & high isolation、 Low polarization-dependent loss and polarization mode dispersion、 Epoxy-free optical path、 Extremely high reliability and stability

- **Part Number**

MP-ISO-F-1310-A-S-PA-1

- **Application area**

Fiber amplifiers、 WDM & DWDM systems、 Fiber optic equipment、 Fiber lasers

- **Core parameters**


Central wavelength	Isolation	Fiber pigtail connector type
1310nm	>28dB	FC/APC

● Dimension Drawing

Standard size fiber isolators



Mini fiber isolators



● General Parameters

Parameters

Parameter	Unit	Value	Remark
Central wavelength (nm)	nm	1550 or 1310	1030/1053/1064/ etc. (Wavelength can be customized)
Operating bandwidth	nm	±15	
Insertion loss	dB	≤0.6	1550nm,30mw,DFB

Isolation	dB	≥28 single stage	@25 Celsius
		≥46 dB dual stage	
Isolation	dB	≥20	Full temperature: -40+75°C
Polarization-dependent loss	dB	≤0.1dB	
Fiber type	N/A	SMF-28E+/PM 1550 ect.(SM or PM)	1030/1053/1064nm optional Hi1060(other fiber types optional)
Polarization film dispersion	Ps	<0.25	
Polarization dispersion	Ps	<0.05	
Return loss (incoming/ outgoing)	dB	>60/55dB	
Maximum operating power	mW	500	
Operating temperature	°C	-5-70°C	
Storage temperature	°C	-40-85°C	
Test light source		1550nm benchtop light source/ 1060nm DFB	



Pakeage size(mm)		As shown below	
------------------	--	----------------	--

Note:

*.All indicators are without connectors and are only valid at the above wavelengths, polarization states and temperatures.

**.Indicators are subject to change without prior notice.

Ordering Information

MP-ISO-F-W-A-S/D-XX-PL

F: fiber coupling

W□□□□: Wavelength

0980:980nm

0850:850nm

1064:1064nm

1310:1310nm

1550:1550nm

A: 500mW

Isolation Class:

S for Single-Stage, D for Dual-Stage

XX: Fiber and Connector Type

SA=SMF-28E+ FC/APC



SP=SMF-28E+ FC/PC

SN= Bare fiber, no connector

PA=PM Fiber+ FC/APC

PP=PM Fiber+ FC/PC

Pigtail Length:

05:0.5m

1: 1m

10:10m