

698nm 200mW DPSS NIR Single Frequency Laser



● Product Description

689/698/813/857nm lasers are specifically designed for deployment in systems utilizing rubidium transitions. With outstanding beam characteristics, ultra-stable output, and an ultra-compact package, they are ideal for demanding applications requiring these wavelengths.

● Product features

Precise wavelength; Single frequency narrow linewidth; Continuous wave output; All solid-state design; Low noise performance

● Part Number

MP-DPSS-698-200

● Application area

Cold atom physics | Quantum simulation | Precision measurement |
Quantum communication | Scientific instruments

● Core parameters

Wavelength	Output Power	Spectral Bandwidth
698nm	200mW	$\leq$ 200kHz

● General Parameters

Detailed Parameters

Parameter	MP-DPSS-6	MP-DPSS-6	MP-DPSS-7	MP-DPSS-81	MP-DPSS-85
	89-50	98-200	80-400	3-200	7-200
Output Power	Up to 50mW	Up to 200mW	Up to 400mW	Up to 200mW	
Wavelength	689.4 nm	698 nm	780 nm	813 nm	857nm
Spectral Width	$\leq 200\text{kHz}$				
Spatial Mode	TEM00				
Spectral Stability	$< 100\text{fm}$ (over > 8 hours operation)				
Coherence Length	$> 100\text{ m}$				
Output Power Stability	$\leq 1.0\%$ (over > 8 hours operation, peak to peak)				
Output Power	$\leq 0.1\%\text{RMS}(10\text{Hz}-10\text{MHz})$				

Noise	
Beam Divergence	1.0 mrad.diffraction-limited
Beam Diameter at Output Aperture	0.8-1.2 mm
Beam Pointing Stability	$\leq 5 \mu\text{rad}/^{\circ}\text{C}$
Laser Head Dimensions	210x100×80 mm
Control Unit Dimensions	180×50×60mm
Ambient Temperature	18-30°C

Range	
Laser Head Interface Stability	$\pm 1.5^{\circ}\text{C}$
Storage Temperature	0-50°C
Humidity	0-50 %non-condensing
Laser Head	Hermetically sealed
Integrated Features	
Plug-and-play USB connection	Integrated heat sink
Multi-function control software	Remote diagnostic support
Optional Accessories	
Heat sink	Fan-assisted air cooling or water-cooled thermoelectric chiller



External manual power control	0-100%, continuous
--	---------------------------

Warranty

12-month warranty for the laser head and controller.

Optional Configurations